

C5225 Vtl CNC Vertical Lathe Machine Diameter 2500MM Four Chuck Double Column

Basic Information

Place of Origin: Henan, China
Brand Name: Baishun
Certification: ISO
Model Number: C5225
Minimum Order Quantity: 1 Set
Price: Negotiation

Packaging Details: Export standard wooden case package

• Delivery Time: 45 working days

Payment Terms: T/T, L/C, Western Union
 Supply Ability: 100Set/Sets per Month



Product Specification

• Condition: New

Type: VERTICAL
Voltage: 380V/50HZ
Warranty: 1 Year
Automatic Grade: Manual
Power: 55KW
Max. Swing Diameter: 2500mm

Key Words: Vertical Lathe Machine

Highlight: C5225, cnc vertical lathe machine,

cnc vtl machine



More Images



Product Description

Four Chuck C5225 2500MM Double Column CNC Vertical Lathe Machine

Product description

The heavy duty vertical lathe machine is one of my company's own developed vertical lathes, belonging to large universal metal-cutting processing equipment. The product uses advanced CAD computer-aided design techniques, in accordance with national, industry-related design and manufacture of acceptance standards.

The heavy duty vertical lathe machines specifics to large electrical motor industry, large pump valve type industries, transportation industry, as well as engineering machinery, defense industries of some large workpieces cylindrical-type parts with diameter less than 4 m, such as the motor shell, the pump valve shell, wheel hub, to conduct turning processes on end face, internal and external cylindrical surface, but also can use vertical tool carrier with spanning degrees (+/-30 degrees) for the internal and external cone turning processing needs.

Features

- 1. The main movement of heavy duty vertical lathe adopts the advanced frequency control system driven by 75Kw variable-frequency motor, through the manual high-low gear shift, so that spindle obtains 2.5 40 r / min stepless speed.
- 2. Table is inlaid with casting zinc, aluminum, copper alloy ZZnA110-5 wearing rail plate to increase the carrying capacity of rail.
- 3. Spindle of worktable is equipped with two high-precision biserial short cylindrical roller bearings; the inner ring has the taper for adjusting the radial clearance, in order to ensure spindle's stable working under high-precision. The manipulation buttons of workbench's startup, braking and jogging are set on the hanging button station.
- 4. Max. swing angle of vertical tool post is +/- 30°, which is used for turning inner and outer cone face.
- 5. Right feed movement adopts advanced variable-frequency speed adjusting system.

Main specification of china cnc fanuc vtl machine

Main specification of china che fanue vit machine						
Item	C(K)5225	C(K)5232	C(K)5235	C(K)5240	C(K)5250	C(K)5260
Work table diameter	2250 mm	2830mm	2830mm	3150mm	4500mm	5200mm
Max. turning diameter	2500mm	3200mm	3200mm	4000mm	5000mm	6000mm
Max. height of work piece(mm)	1600- 2800	1600- 3000	1600- 3000	1600- 3200	2500-4200	2500-4500
Max. weight of work piece	10/20	10/20/32	10/20/32	10/20/32	32/50	32/50
Max. torque of worktable	63000 N•m	63000 N•m	63000 N•m	63000 N•m	105000N•m	105000N•m
Rest feeding range	0.25-90 mm/min	0.25-90 mm/min	0.25-90 mm/min	0.25-90 mm/min	0.1-1000 mm/min	0.1-000 mm/min
Beam travel	1250mm	1250mm	1250mm	1250mm	2150mm	2150mm
Horizontal Travel of tool rest	1400mm	1750mm	1900mm	2150mm	2700mm	3300mm
Vertical Travel of tool rest	0/	0/	1000/125 0/ 1400/160 0	1000/125 0/ 1400/160 0	1400/1600	1400/1600
Beam moving speed(mm/min)	350	350	350	350	380	380
Max. Swing angle of tool post	±30°	±30°	±30°	±30°	±30°	±30°
Turret dimension(WxHmm)	40x50	40×50	40×50	40x50	60x65	60x65
Main motor power	55kw	55kw	55kw	55/75kw	75kw	75kw
Machine Weight(around)	33-38T	36-50T	38-62T	43-65T	92-105T	150-200T

Machine picture





Henan Baishun Machinery Equipment Co., Ltd.







lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China