



CK5225 Automatic CNC Vertical Lathe Machine for Metal Turning

Our Product Introduction

for more products please visit us on lathemach.com

Basic Information

- Place of Origin: China
- Brand Name: BAISHUN
- Certification: ISO
- Model Number: CK5225
- Minimum Order Quantity: 1 set
- Price: Negotiation
- Packaging Details: Export standard wooden case package or Negotiation with customers
- Delivery Time: 70 work days
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 50 Set/Sets per Month



Product Specification

- Condition: New
- Type: VERTICAL
- Max. Weight Of Workpiece(kg): 8000
- Max. Turned Length (mm): 2000
- Travel (X Axis)(mm): 1100 Mm
- Travel (Z Axis)(mm): 2000 Mm
- Positioning Accuracy (mm): ± 0.002
- Repeatability (X/Y/Z) (mm): ± 0.001
- Weight (KG): 23000
- Key Selling Points: Automatic
- Highlight: cnc vertical metal turning lathe,
automatic vertical metal turning lathe,
CK5225 vertical metal turning lathe



More Images



Product Description

CK5225 automatic vertical metal turning lathe cnc vertical lathe machine

Machine description

This CNC vertical lathe machine cutting action is controlled by the CNC controller, and the feeding axis is driven by the AC asynchronous servo motor, with a touch screen display and hand-held pulsed. The main transmission is driven by the spindle AC servo motor, hydraulic gear change and two gears step-less speed regulation. Worktable is a manual 4-jaw single movement chuck.

The CNC vertical lathe is a top-performing machine with a wide range of capabilities and high productivity. Our company has developed a cutting-edge machine tool that seamlessly integrates animatronics and hydraulics, drawing inspiration from advanced design and manufacturing techniques, and incorporating our rich corporate culture. This allows us to deliver world-class products to both domestic and international customers.

Product Features:

- 1.This CNC Vertical lathe is suitable for the industries of mechanical processing, can be used for inside and outside the cylinder, cone surface and face, cutting, cutting, etc. Of course and fine turning processing.**
- 2.Workbench using hydro static guideway, the main shaft adopt high precision NN30 type (D) double row cylindrical roller bearing, thus workbench large carrying capacity, high rotary precision.**
- 3. Machine tool electric using domestic brand-name products, high reliability.**
- 4.Machine is made of high qualified EPC process, high quality, the annealing aging treatment, appearance beautiful, durable, good agreeableness, convenient operation and maintenance.**

Product Parameters:

Model	CK518	CK5112 Q	CK5112 A	CK5116 Q	CK5116 A	CK5120 A	CK5126 A
Max. turning diameter (mm)	800	1200	1200	1600	1600	2000	2600
Working table diameter (mm)	700	1000	1000	1400	1400	1800	2200
Max. height of work-piece (mm)	800	1000	1000	1200	1200	1250	1400
Max. weight of work-piece (kg)	1500	1500	3200	3200	5000	8000	8000
Range of worktable rotation speed (rpm)	30-260	20-180	6.3-200	15-160	5-160	3.2-100	2.2-170
Feeding series	Stepless	Stepless	Stepless	Stepless	Stepless	Stepless	Stepless
Range of tool rest feed (mm/min)	0.25-90	0.25-90	0.8-86	0.25-90	0.8-86	0.8-86	0.8-86
Cross beam travel (mm)	500	1000	650	1200	650	890	1090
Horizontal travel of tool rest (mm)	500	700	700	900	916	1115	1400

Vertical travel of tool rest (mm)	450	500	650	750	800	800	800
Size of section of cutter bar (mm)	30*40	30*40	30*40	30*40	30*40	30*40	30*40
Main motor power (kw)	11	15	22	15	30	30	30

Machine picture





Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China