



CNC Wheel Cutting Vertical Lathe Machine 15kW Single Spindle

Our Product Introduction

for more products please visit us on lathemach.com

Basic Information

- Place of Origin: Henan, China
- Brand Name: BAISHUN MACHINERY, BAISHUN MACHINERY
- Certification: ISO
- Model Number: CK5112
- Minimum Order Quantity: 1 set
- Price: Negotiation
- Packaging Details: Export standard wooden case package or Negotiation with customers
- Delivery Time: 45 work days
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 50 Set/Sets per Month



Product Specification

- Product Name(mm): CNC Wheel Cutting Vertical Lathe Machine
- Machining Capacity: Medium Duty
- Spindle Motor Power(kW): 15
- No. Of Spindles: Single
- Max. Turned Length (mm): 1200
- Positioning Accuracy (mm): ± 0.005
- Repeatability (X/Y/Z) (mm): ± 0.005
- Voltage: 380V
- Product Name: CNC Wheel Cutting Lathe Machine
- Highlight: **Automatically Vertical Lathe Machine**



More Images



Product Description

Product Description

Vertical Turning Lathe Automatically CNC Wheel Cutting Lathe Machine

The CNC vertical lathe, also known as a vertical turning center, is a machine tool used for turning and cutting metal components with high precision and efficiency.

CNC vertical lathe has a vertical spindle that holds and rotates the workpiece. They are widely used in the manufacturing industry for producing large and heavy components, such as gears, turbines, and aerospace parts. They are particularly useful for turning components with a high aspect ratio.

Additionally, CNC vertical lathes are highly automated and can be programmed to perform a wide range of machining operations, such as turning, drilling, boring, threading, and milling, with minimal human intervention.

Overall, The CNC vertical lathes are a versatile and efficient machining tool that offer high precision and automation capabilities, and that is why makes them an essential component of modern manufacturing processes.

Our hot selling CNC Vertical Turning Lathe is perfect for processing ferrous metals, nonferrous metals, and some non-metallic materials. It can handle tasks such as turning end faces, inner and outer cylindrical surfaces, inner and outer circular conical surfaces, as well as hole drilling, expanding, and reaming. The main transmission is driven by an AC servo motor, and the machine offers hydraulic gear shifting and stepless speed regulation with two gears. The worktable is equipped with a manual 4-jaw single movement chuck for easy operation.

Key Features:

1. Our CNC vertical lathe is equipped with the Siemens 828DD system, ensuring precise control. It features a vertical tool post, allowing for a maximum machining diameter of 1600mm, a table diameter of 1400mm, and a maximum machining height of 1000mm.
2. The transmission device adopts a four-speed continuous transmission, providing convenience, sensitivity, and reliability.
3. All gears in the system are made of 40Cr grinding gears, guaranteeing high rotation accuracy and minimal noise.
4. This machine is suitable for processing non-ferrous metals, black metals, and non-metallic materials using high-speed steel tools and carbide cutting tools. It can perform various operations, including turning inner and outer cylindrical surfaces, cutting different types of faces (such as hooks), inner and outer conical surfaces, threading, as well as slotting and cutting.

Machine parameter

Model	CK518	CK5112Q	CK5112A	CK5116Q	CK5120A	CK5126A
Max. turning diameter of vertical tool rest (mm)	800	1200	1200	1600	2000	2600
Working table diameter (mm)	700	1000	1000	1400	1800	2200
Max. height of work-piece (mm)	800	1000	1000	1200	1250	1400
Max. weight of work-piece (kg)	1500	1500	3200	3200	8000	8000
Range of worktable rotation speed (rpm)	30-260	20-180	6.3-200	15-160	3.2-100	2.2-70
Feeding series	Stepless	Stepless	Stepless	Stepless	Stepless	Stepless
Range of tool rest feed (mm/min)	0.25-90	0.25-90	0.8-86	0.25-90	0.8-86	0.8-86
Cross beam travel (mm)	500	1000	650	1200	890	1090
Horizontal travel of tool rest (mm)	500	700	700	900	1115	1400
Vertical travel of tool rest (mm)	450	500	650	750	800	800
Size of section of cutter bar (mm)	30*40	30*40	30*40	30*40	30*40	30*40
Main motor power (kw)	11	15	22	15	30	30

HIGH EFFICIENCY CK5112 CNC VERTICAL LATHE



IT'S TIME TO
GET YOUR MACHINE

MULTI-PURPOSE | CNC LATHE

High Quality /PRODUCT⁺

Factory Diresct /SELLING⁺

Whatsapp: +86 18003851898
Email: dora@bsmachinery.com

Product Details Display

01

WORKTABLE

Worktable has high rotation precision and large load capacity.



WhatsApp: +86 18003851898

03

COLUMN/ CROSS BEAM

High frequency column and beamguide, hardness HRC-55 degree.



02

ELECTRIC TOOL POST


Clients can choose 4,5,6 station electric tool post.



04

CONTROL SYSTEM

Standard with GSK980TDi control
Optional: Siemens, Fanuc, Syntec ect.



WhatsApp: +86 18003851898



Henan Daishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China