

# Metal Turning CNC Vertical Lathe Machine

## **Basic Information**

• Place of Origin: Henan, China

Brand Name: BAISHUN MACHINERY, BAISHUN

MACHINERY

Certification: CE/ISO9001
Model Number: CK5116
Minimum Order Quantity: 1 Set
Price: Negotiable

Packaging Details: Export standard wooden case package or

Negotiation with customers

• Delivery Time: 30-35 work days

Payment Terms: L/C, T/T, Western UnionSupply Ability: 20 Set/Sets per Month



# **Product Specification**

 Max. Length Of Workpiece 1600 (mm):

Max. Spindle Speed (r.p.m):160 R.p.m
Machining Capacity: Medium Duty
No. Of Spindles: Single

Max. Turned Length (mm): 1600Repeatability (X/Y/Z) (mm): ±0.004

• Dimension(L\*W\*H): 2660\*2665 \*3528mm

Product Name: Cheap Cost CNC Vertical Turing Lathe

Machine

• Highlight: Turning CNC Vertical Lathe Machine,

Metal CNC Vertical Lathe Machine,

**Metal Vertical Lathe** 



# More Images



## **Product Description**

#### CK5116 CNC Vertical Lathe

#### Main Features:

- 1. CNC vertical lathe, the CNC system uses Siemens 828DD system, there is a vertical tool post, the maximum machining diameter is 1600mm, the table diameter is 1400mm, and the maximum machining height is 1000mm.
- 2. The transmission device is a four-speed sleepless transmission, which is convenient, sensitive and reliable.
- 3. Set in the system, all gears use 40Cr grinding gears, which have the characteristics of high rotation accuracy and low noise.
- 4. The machine is suitable for high speed steel tools and carbide cutting tool processing of non-ferrous metal, black metal and nonmetal materials. On the machine can complete the following processes:Turning the inner and outer cylindrical surface of the plane; all kinds of hook face, inner and outer cone face, thread, cutting slot and cutting.

### **Product Description**

The CNC vertical lathe, also known as a vertical turning center, is a machine tool used for turning and cutting metal components with high precision and efficiency.

CNC vertical lathe has a vertical spindle that holds and rotates the workpiece. They are widely used in the manufacturing industry for producing large and heavy components, such as gears, turbines, and aerospace parts. They are particularly useful for turning components with a high aspect ratio.


Additionally, CNC vertical lathes are highly automated and can be programmed to perform a wide range of machining operations, such as turning, drilling, boring, threading, and milling, with minimal human intervention.

Overall, The CNC vertical lathes are a versatile and efficient machining tool that offer high precision and automation capabilities, and that is why makes them an essential component of modern manufacturing processes.

#### Machine parameter

Model	CK518	CK5112Q	CK5112A	CK5116Q	CK5120A	CK5126A
Max. turning diameter of vertical tool rest (mm)	800	1200	1200	1600	2000	2600
Working table diameter (mm)	700	1000	1000	1400	1800	2200
Max. height of work-piece (mm)	800	1000	1000	1200	1250	1400
Max. weight of work-piece (kg)	1500	1500	3200	3200	8000	8000
Range of worktable rotation speed (rpm)	30-260	20-180	6.3-200	15-160	3.2-100	2.2-70
Feeding series	Stepless	Stepless	Stepless	Stepless	Stepless	Stepless
Range of tool rest feed (mm/min)	0.25-90	0.25-90	0.8-86	0.25-90	0.8-86	0.8-86
Cross beam travel (mm)	500	1000	650	1200	890	1090
Horizontal travel of tool rest (mm)	500	700	700	900	1115	1400
Vertical travel of tool rest (mm)	450	500	650	750	800	800
Size of section of cutter bar (mm)	30*40	30*40	30*40	30*40	30*40	30*40
Main motor power (kw)	11	15	22	15	30	30





+8618939515188

sale@goodlathe.com



athemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China