

CNC Vertical Lathe 3500mm Turning Diameter 55kW Twin Spindle

Basic Information

• Place of Origin: Henan, China

Brand Name: BAISHUN MACHINERY

Certification: CE ISO
Model Number: CK5235
Minimum Order Quantity: 1 Set
Price: Negotiable


• Packaging Details: 1. Outside we will pack the product with

plasitic to prevent wet.2. Outside of the cnc vertical lathe machine will be packed by

strong wooden pallet.

• Delivery Time: 30-35 work days

Payment Terms: L/C, T/T, Western Union
 Supply Ability: 20 Set/Sets per Month



Product Specification

Max. Length Of Workpiece 2500 (mm):

• Max. Spindle Speed (r.p.m):90 R.p.m

Machining Capacity: Medium Duty

Spindle Bore(mm): 105
Width Of Bed (mm): 250 Mm
Spindle Motor Power(kW): 55
No. Of Spindles: Twin
Number Of Axes: 2

Travel (X Axis)(mm): 1900 Mm
Travel (Z Axis)(mm): 1250 Mm
Positioning Accuracy (mm): ±0.005
Repeatability (X/Y/Z) (mm): ±0.003

Dimension(L*W*H): 6150*4400*5330mm

• Voltage: 380V



More Images









Product Description

New Design Metal Manual Heavy Duty Lathe Double Columns Vertical Turning Lathe

The double column vertical lathe is a cutting-edge piece of equipment that combines mechanical, electrical, and hydraulic components. It incorporates modern design principles and manufacturing techniques, leveraging CAD optimization and state-of-the-art components from both domestic and international sources. The machine boasts a robust structure, offering exceptional strength, high static and dynamic stiffness, precise machining capabilities, heavy load capacity, efficiency, durability, and reliable operation. All major technical specifications of the machine parts comply with national standards.

The machine consists of various components, including the worktable base, worktable, main transmission box, gantry frame, beam, ram tool rest, feeding box, electrical system, operation station, hydraulic system, and protection devices.

Double column vertical lathe is an advanced equipment with the integration of mechanical-electrical-hydraulic, which absorbing the new design philosophy and manufacturing technology. It adopts the CAD optimization design way, equips advanced functional components at home and abroad. In structure, it achieves strong strength, high dynamic and static stiffness, high precision, heavy loading, high efficiency, long service life, safe and reliable movement. Main technical specifications of each machine parts conform to the national related standards.


Machine has worktable base, worktable, main transmission box, gantry frame, beam, ram tool rest, feeding box, electrical system, operation station, hydraulic system, protection device and so on.

Machine parameter

Specifications	Unit	CK5225	CK5231	CK5240Q	CK5240
Max.turning diameter	mm	2500	3150	4000	4000
Max. height of work piece	mm	1600/2000/2500	1600/2000/2500	1600/2000/2500	1600/2000/2500
Max. weight of work piece	Т	10/20	10/20	10/20	32
Worktable diameter	mm	2250	2830	2830/3150	3200/3600
Range of table speeds	r/min	2-63	2-63	2-63	2-63
Steps		16	16	16	16
Max torque of work table	KN.m	63	63	63	100
Rapid traverse of rail head	mm/min	4000	4000	4000	4000
Ram vertical travel of right railhead	Kn	35	35	35	40
Ram vertical travel of left railhead	kn	30	30	30	30
Range cutting force of right railhead	mm/min	1-50	1-50	1-50	1-50
Range cutting force of right railhead	mm/min	0.1-1000	0.1-1000	0.1-1000	0.1-1000
Travel of arm	mm	1000	1000	1000	1250
Section of arm	mm	255×200	255×200	255×200	240×240
Swivel of left and right railhead	0	±30°	±30°	±30°	±30°
Section of tool	mm	40×50	40×50	40×50	50×50
Power of main motor	Kw	55	55	55	75
Overall dimensions	cm	569×470×480/520	605×440×493/533	690×510×480/520	690×510×480/520

Product photos









Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China