



## 1250mm CK64125 Cnc Face Turning Lathe Flange Turning Machining

Our Product Introduction

for more products please visit us on lathemach.com

### Basic Information

- Place of Origin: Henan, China
- Brand Name: Baishun
- Certification: ISO9001:2008
- Model Number: CK64125
- Minimum Order Quantity: 1 set
- Price: Negotiation
- Packaging Details: Export standard wooden case package or Negotiation with customers
- Delivery Time: 45 work days
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 80 Set/Sets per Month



### Product Specification

- Type: Floor Type
- Voltage: 3 Phase 380V 50HZ
- Dimension(L\*W\*H): 4200\*2200\*1950mm
- Max. Turning Diameter: 1250mm
- Chuck Diameter: 1000mm
- Keyword: Cnc Face Lathe
- Max Swing Over Bed: 1250mm
- Usage: Flange Facing
- Weight: 6000kg
- Max. Swing Diameter: 1250mm
- Power(W): 11KW
- Highlight: CK64125, face turning lathe, Cnc Face Turning Lathe



### More Images



## Product Description

1250mm Turning Diameter CK64125 Cnc Face Lathe Machine For Flange Turning And Machining

### Specifications

standing facing lathe machine  
High quality with low price  
Operate simple, performance stable  
ISO9001:2008 Certification  
Standing lathe

#### 1. Function characteristics

The company produces various models of ground lathe also named face lathe machine; also produce horizontal lathe machine, vertical lathe, with the weight of large, rigid, and easy to operate, powerful, and many other advantages. And has a CNC vertical lathe, boring machine large landing, automatic gap submerged arc welding, electro-optical tracking cutting machine and a variety of measurement test equipment. Besides, using the vertical lathe to turn vanes can eliminate the defects that a floor-type horizontal machine is low in rotary speed, unstable in slewing and the like.

landing facing lathe machine is mainly used to process large, medium plate and cylinder workpiece such as flange, valve, gland, plate, motor cover, tire mold, etc.  
This lathe can be widely applied in the production field of energy, transportation, oil, chemical industry, mining, railway, car making and so on.

1. Geared Head Engine Lathe is floor face lathe, mainly suitable for high-speed steel or carbide cutting tools, cast iron, steel, forgings and non-ferrous disc type rotating body metal parts machining.
2. To complete the cylindrical, conical, end, grooving and other machining processes, can meet part of the rough and fine turning.
3. All the gears are precision grounded, with long life and low noise;
4. All guideways are quenched and hardend, protection covers equipped for the guideways, free from the chips falling on the guideways, ensuring feed precision and speed.

□□□□

#### Description of Flange Facing lathe machine:

This Flange Facing lathe or landing lathe is mainly used to process large, medium plate and cylinder workpiece such as flange, valve, gland, plate, motor cover, tire mold, etc.  
This lathe can be widely applied in the production field of energy, transportation, oil, chemical industry, mining, railway, car making and so on.

1. Flange Facer is floor face lathe, mainly suitable for high-speed steel or carbide cutting tools, cast iron, steel, forgings and non-ferrous disc type rotating body metal parts machining.
2. To complete the cylindrical, conical, end, grooving and other machining processes, can meet part of the rough and fine turning.
3. All the gears are precision grounded, with long life and low noise;
4. All guideways are quenched and hardend, protection covers equipped for the guideways, free from the chips falling on the guideways, ensuring feed precision and speed.

#### Technical Parameters:

Parameters	unit	CK64125
Max. Swing diameter over bed	mm	1250
Max. Swing diameter over cross slide	mm	900
Four jaws chuck diameter	mm	1000
Max. length of work piece	mm	550
Max. weight of work piece	kg	2000
Horizontal travel of Cross slide	mm	650
Longitudinal travel of Cross slide	mm	350
Rapid move speed of Carriage	Mm/min	1000
2 axis Servo motor torque		11/16
Main spindle rotate speed series	kinds	2
Main spindle speed	r/min	10-200
Spindle diameter (Bearing front-end)	mm	180

Power of main motor	kw	15
CNC control system		GSK980TDc/Siemens808D
Other configuration	Equip electric 4-position tool post changer.	

Note: If you need manual kind face lathe machine, please see following specification:

Item	Unit	C6010	C6016	C6020	C6025	C6030
Chuck diameter	mm	800	1200	1600	2000	2500
Max. turning diameter	mm	1000	1600	2000	2500	3000
Max. length of work pieces	mm	200	400	600	600	600
Max weight of workpiece	T	1	2	3	3	5
Power of main motor	kW	15	11	15	15	22
Spindle speed	r/min	8-120	16-128	12-94	12-94	4-40
Spindle diameter	mm	190	200	200	200	300
Feed way of tool rest	Infinitely variable frequency					
Horizontal stroke	mm	320	320	320	320	320
Longitudinal travel	mm	500	800	900	1400	1400
Weight	T	4	5	8	10	17

#### Packaging & Shipping

□□  
□□□□

#### Our Services

##### **Our Service:**

- 1.Any inquiries will be replied within 12 hours
  - 2.Professional manufacturer, Welcome to visit our factory at any time
  3. OEM services are welcomed, and we can help you to print your logo, company information etc on our products and package
  - 4.High quality, fashion designs, reasonable & competitive price and fast lead time
  - 5.After-sale service
  - 6.Faster delivery
  7. Protection of your sales area, ideas of design and all your private information
- You can pay for the order via: T/T, western union, L/C at sight.  
Our ultimate goal is your satisfaction!

#### Contact Way

□



**Henan Baishun Machinery Equipment Co., Ltd.**



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China