# Y3150E Gear Hobbing Milling Machine Cnc Gear Hobber

Henan Baishun Machinery Equipment Co., Ltd

Henan, China

BAISHUN

Negotiation

45 work days

50 Set/Sets per Month

ISO


Y3150

1 set

## **Basic Information**

lathemach.com

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



## **Product Specification**

CNC Or Not:	CNC
Condition:	New
• Туре:	Gear Hobbing Machine
• Video Outgoing-inspection:	Provided
<ul> <li>Machinery Test Report:</li> </ul>	Provided
<ul> <li>Marketing Type:</li> </ul>	New Product 2021
Warranty Of Core     Components:	1 Year
Core Components:	Engine, Bearing, Gearbox, Motor
• Voltage:	380V/50Hz
<ul> <li>Dimension(L*W*H):</li> </ul>	2440 X 1370 X 1800
• Warranty:	1 Year, 12 Months
<ul> <li>Key Selling Points:</li> </ul>	High-accuracy
• Weight (KG):	4500
• Power (kW):	4



## More Images



#### Product Description

Gear Hobbing Machine Price Gear Hobs Cutter Hob Gear Milling Machine Y3150E

**Product Description** 

Gear Hobbing Machine Price Gear Hobs Cutter Hob Gear Milling Machine Y3150E

The machine has the following characteristics:

Raised height for vertical column and increased stroke: The vertical column is made higher (180/130mm increased axial stroke in head slide than Y3180/Y3150 of the same kind) to enable processing of larger tooth width. Service life of cutting tools is increased by electric tool leap. The longest stroke reaching 180mm, such electric tool leap takes

longer hob and greatly increases life the hob.

High precision and long service life: The machine adopts the worm gear of a high precision over five grade and uses bronze alloy material which is of high abrasion resistance, enabling long service life and steady accuracy. Higher tool speed allowed: Rolling bearings replace the traditional bearings along the hobs to allow greater rotating speed of the tools.

Backlash balancing cylinder is involved as the tool post moves in the axial direction, effectively reducing the space between lead screws and eliminating vibration.

Technical Parameter	Unit	Y3150E
Max work piece diameter	mm	500
Max modulus	mm	8
Max machining width	mm	250
Min machining number of teeth		6
The largest machining spiral angle		+-45
Scope of main tool turning speed and grade	rpm/grade	40-250/9
Max turning angle of tool		240
Max tool loading dimensions(diameter* length)	mm	160 *160
Main motor	kw	6.45
Spindle taper		Morse 5
Max axial amount of movement of tool	mm	50
Distance between axis line of tool and worktable face	mm	235-535
Min distance between tool axis and worktable axis	mm	30
Distance between back rest under face and worktable face	mm	380-630
Machine size(length* width* height)	mm	2440*1370* 1800
Weight	kg	4500

Product photos for your reference:





### Our Services

24 Hours after sales service by E-mail or Phone.
 100% response rate.

3. Engineers availab	to service overseas.	
4. OEM service is av	lable	
5. Warranty: 12 mon	s, beyond the warranty period, all spare parts offered to you withfactory price.	
	Henan Baishun Machinery Equipment Co., Ltd.	
	<ul> <li>Henan Baishun Machinery Equipment Co., Ltd.</li> <li>+8618939515188 Sale@goodlathe.com Itathemach.com</li> </ul>	