



## B5020 Manual Type Keyway Slotting Tools Rapid Feed Vertical Planer

Our Product Introduction

for more products please visit us on [lathemach.com](http://lathemach.com)

### Basic Information

- Place of Origin: China
- Brand Name: Baishun
- Certification: ISO
- Model Number: B5020
- Minimum Order Quantity: 1 Set
- Price: Negotiation
- Packaging Details: Export standard wooden case package
- Delivery Time: 20 working days
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 100Set/Sets per Month



### Product Specification

- Name: Metal Slotting Machine
- Video Outgoing-inspection: Provided
- Machinery Test Report: Provided
- Controller: PLC
- Voltage: 380v/50hz Or As Customer Required
- Warranty: 1 Year
- Power (kW): 4
- Weight (KG): 2200 KG
- Model: B5020
- Function: Metal Slotting
- Highlight: B5020, keyway slotting tools, keyway slotting



### More Images



## Product Description

### B5020 Rapid Feed Vertical Planer Keyway Processing Metal Slotting Machine

The main performance characteristics:

- 1.The working table of the machine tool is provided with three different directions of feed (longitudinal, horizontal and rotary), therefore work object go through once clamping, Several surfaces in the machine tool machining
  - 2.Hydraulic transmission mechanism with sliding pillow reciprocating motion and hydraulic feed device for working table.
  - 3.The sliding pillow has the same speed in every stroke, and the movement speed of the ram and the working table can be adjusted continuously.
  - 4.Hydraulic control table have ram commutation oil for oil reversing mechanism, In addition to hydraulic and manual feed outer,
- Even there single motor drive vertical, horizontal and rotary fast moving.
- 5.Use hydraulic feed the slotting machine, Is when the work is over turning back instantaneous feed, Therefore be better than mechanical slotting machine used drum wheel feed.

Application:

1. This machine be used for interpolation plane, forming surface and Keyway Etc. And can insert the inclination in the 10° Mold and other within the scope of etc. work matter,,
2. Enterprise suitable for single or small batch production.

#### Product main technical parameters:

Specification	Unit	B5032	B5020
Max. stroke of RAM	mm	340	220
Ram maximum slotting length	mm	320	200
Ram motion frequency	times/min	20.32.50.80	32.50.80.125
Ram tilt angle	°	0-8	0-8
Ram vertical adjustment distance	mm	315	230
Cutter head bearing surface to the distance between the forearm bed	mm	600	485
Table Diameter	mm	630	500
The distance between the lower end of the sliding frame to work table	mm	490	320
Max. longitudinal moving distance of working table	mm	630	500
Max. transverse moving distance of working table	mm	560	500
Table maximum rotation angle	°	360	360
Vertical and horizontal table power feed range	mm	0.08-1.21	0.08-1.21
Table rotary feed range	mm	0.052-0.783	0.052-0.783
Motor power	kw	4	3
Motor speed	r/min	960	1430
Machine weight	kg	3000	2200
Outline dimension	mm	2261*1495*2245	1916*1305*1995

Machine picture



**河南百顺机械设备有限公司**

**Henan Baishun Machinery Equipment Co., Ltd.**  
Office Address: No. 65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China

**Ms. Elena Xie**  
(Sales Manager)

Ph:/Whatsapp: +86 17838375098

Email: elena@goodlathe.com

Tel:+86 371-55661885



**Henan Baishun Machinery Equipment Co., Ltd.**



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China