

Metal Cutting Automatic Alloy Wheel Slant Bed CNC Lathe Machine TCK550

Basic Information

Place of Origin: CHINA
Brand Name: BAISHUN
Certification: ISO
Model Number: TCK550
Minimum Order Quantity: 1 Set
Price: Negotiable

Packaging Details: Export standard wooden case package

• Delivery Time: 30-35 work days

• Payment Terms: L/C, T/T, Western Union

Supply Ability: 50 Set per Month



Product Specification

Max. Spindle Speed:
 Alloy Wheel Slant Bed CNC Lathe Machine

270mm

 Max. Rotating Diameter 540mm Over Bed:

O 701 DOG.

Max. Turning Diameter
 Over Slider

Over Slide:

Max. Processing Length: 700mm
Positioning Accuracy: ±0.016mm
X Travel: 220mm

• Z Travle: 750mm

Applicable Industries: Metal Working Plant

Tailstock: Manually
Power: 7.5kw
Machine Weight: 3800mm
Package: Customized

• Highlight: Wheel Slant Bed CNC Lathe Machine, TCK550,

Slant Bed CNC Lathe Machine TCK550



More Images



Product Description

High Precision Metal Cutting Automatic Alloy Wheel Slant Bed CNC Lathe Machine

TCK series CNC horizontal slant bed lathe machine is a high-quality product designed and produced in accordance with the market and development needs based on the experience of our factory in designing horizontal CNC horizontal lathes for many years. This machine tool has a maximum diameter of φ360mm and a maximum length of 500mm for machining. We have upgraded the TCK50 series machines with a newly designed mainframe structure and a reliable assembly process. With its stable performance and innovative ergonomic design, the TCK50 series will undoubtedly become an industry leader. This lathe can handle shafts, discs, threads, arcs, cones, and both inner and outer surfaces of rotating objects. We have carefully matched the rigidity of the main spindle, bed, and tailstock to greatly improve the overall stability during heavy cutting. As a result, the machining accuracy of the outer circular surface can reach IT6 to IT7 level. This versatile machine tool is especially suitable for efficient, large-scale, and high-precision machining of rotating parts in industries such as automotive, electrical, bearing, and hydraulic.

Product Parameters

MAIN TECHNICAL DATA		Unit	TCK550	TCK40-750	TCK40-1000
The scope of work	Maximum rotating diameter on the bed	mm	Ø540	Ø540	Ø540
	Maximum turning diameter on the slide	mm	Ø270	Ø270	Ø270
	Maximum processing diameter	mm	Ø400	Ø400	Ø400
	Maximum processing length	mm	700	700	900
Spindle	Maximum spindle speed	r/min	4000	4000	4000
	Spindle runout	mm	0.008/300	0.008/300	0.008/300
	Spindle through hole diameter	mm	Ø65	Ø65	Ø65
	Bar capacity	mm	Ø48	Ø48	Ø48
	Hydraulic chuck	inch	8	8	8
	Spindle motor power	kw	7.5	7.5	7.5
stroke	X-axis travel	mm	220	220	220
	Z-axis travel	mm	750	750	1000
Feed	X axis fast moving	m/min	20	20	20
	Z axis fast moving	m/min	20	20	20
	Cutting feed	mm/min	1-6000	1-6000	1-6000
Tail	Tail stock stroke	mm	550/manual	550/manual	800/manual
stock	Tail stock sleeve stroke	mm	120/ hydraulic/manual		
Guide	Bed rail tilt angle	Deg.	30	30	30
	Туре		Liner guideway	Liner guideway	Liner guideway
Precisio	positioning accuracy	mm	0.016	0.016	0.016
n	Repeatability	mm	0.008	0.008	0.008
Other	Machine weight	kg	3800	3800	4200
	Dimensions	mm	2920x1680x2 070	2920x1680x2 070	3200x1680x2070

Machine pictures:







CNC SYSTEM



Main Configuration



Hydraulic chuck

Ball screw and line track

A convex and a flat tailstock design

Assembly Process and Quality Control









Screw installation process



Electrical system configuration box



Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China