

Steel CNC Roll Lathe Metal Milling Roll CK8450

Basic Information

Place of Origin: China
Brand Name: BAISHUN
Certification: CE ISO
Model Number: CK8450
Minimum Order Quantity: 1 Set
Price: Negotiable

Packaging Details: Export standard wooden case package

• Delivery Time: 30-35 work days

• Payment Terms: L/C, T/T, Western Union

• Supply Ability: 50 Set per Month



Product Specification

Product Name: High Precision Roll Turning Lathe Machine

Price

Model: CK8450
Max. Swing Diameter: 500mm
Max. Turning Length: 2500mm
Function: Roll Turning
Main Motor Power: 22KW
Application: Metal Works

CNC System: SIEMENS
Machine Weight: 8500KG
Color: Customized

Highlight: steel roll lathe, roller lathe, cnc roll lathe



More Images



Product Description

Metal Milling Roll CK8450 CNC High Precision Roll Turning Lathe Machine price

Product Description

This series Professional Roll Turning CNC Lathe Machine can utilize high-speed steel and carbide cutting tools to finish rough or finish turning process for not only the non-ferrous metals like various structure steels, casting steels and irons, but also the external/internal cylindrical / conical/ spherical surfaces, thread of non-metal materials and all kinds of the surface of curve rotary body.

This horizontal cnc lathe machine is suitable for high-speed steel and carbide cutting tool to implement coarse and fine stock removing and cutting on the outer cylindrical surface of roller of different materials; it also can be used for rough and finish machining of various metal parts.

With its dual functions of turning and grinding, the roll turning lathe machine can complete the machining of a part in a single operation, reducing the need for multiple clamping and enhancing overall work efficiency for customers.

All components of machine are imported foreign famous brands, such as FANUC or SIMENS Control System/ Schneider Electrical Control system, Japanese Bearing, ABB Motor& transmission box/gear box, etc. We can also configurate per customer's special request and demands. Our Engineers can design different configurations according to different workpieces characteristics.

Main Features:

- 1. High rigidity and heavy duty lathe frame: It is made of HT300 cast iron and has three guideways.
- 2. High precison ball screw and NSK bearing
- 3. Siemens control system or other CNC system can be choosed.
- 4. It has functions of Milling and Turning, including screw thread, conical surface, curved surface, internal boring, etc.
- 5. This lathe adopts frequency control system as its main drive system
- 6. and the main spindle front bearing adopts high-precision double row cylindrical roller bearings, having high-degree of rigidity and rotary precision and easy to adjust.

Technical Specification

Main nananatana	I I I i i i i	01/0450	0.40400	C A O 4 O O
Main parameters	Unit	CK8450	CA8463	CA8480
Max.turning diameter	mm	500	630	800
Max. turning length	mm	2500	3500	4000
Center height	mm	320	380	550
Max. Weight of workpiece	kg	3500	6500	14000
Range of spindle speed	r/min	1-112	1-75	1-31.5
Number of spindle speeds		16	16	16
Max. Cutting force	KN	40	60	70
Max. Torque of face plate	KN.m	10	25	55
The tailstock sleeve travel	mm	150	200	300
Main motor power	kw	15	22	37
Overall dimensions	mm	5155X1368X1400	7100X1600X1550	9240x2280x180 0
Machine weight	kg	7500	14000	28000









河南百顺机械设备有限公司

(BAISHUN) Henan Baishun Machinery Equipment Co., Ltd.





CK8450 数控轧辊车床



A Professional Roll Processing Equipment Design and Manufacturing Unterprise











© → M→ TGNET CE CK8450 数控轧辊车床 CKCROLLTURNING LATHE

机床用途 Use of Machine Tool





主要技术参数 Main Technical Parameters

項目ten	CK8450	CK8465	CK8480
最大工件直径 Maximum Workpiece Clameter	Ф650mm	Ф650mm	Ф800mm
華大工件长度 Maximum Workpiece Length	2500mm	3500mm	4000mm
中心 Center Height	360mm	440mm	650mm
頂尖间最大工件重量 Maximum Workpiece Weight	3500Kg	7000Kg	14000Kg
華大切耐力 Meximum Cuting Force	20KN	40KN	SOKN
花盘最大扭矩 Maximum Torque of Fecepiate	10KN.m	12KN.m	16KN.m
主轴转速范围 Range of Spindle Speed	3~350r/min	3-315r/min	3~250t/min
主轴转速级数 Number of Steps of Spinote Speed	无规 Stepless	无键 Steptens	天坂 Stapless
主轴变速方式 Spride Speed Charge Middle	液压自动 Hydracic Automatic	液压剂动 Hydraulic Automatic	液压自动 Hydraulic Automatic
设盘直径 Faceptele Distreter	@500mm	Φ650mm	Φ800mm
连绘量级数 Number of Steps of Feeds	无极 Stepless	无极 Stepless	无极 Stepiete
協向(Z 轴)进始速度范围 Longitudinal (Z Avis) Feed Speed Range	1-2000mm/min	1-3500mm/min	1-3000mm/min
横向 (X 轴) 进始速度范围 Horizontal (X Axis) Feed Spreed Range	1-1500mm/min	t~1500mm/min	1~1500mm/min
尾座套筒移动量 Moving Amount of Tailatock Sleeve	150mm	150mm	300mm
交流变频主电机(功率) AC Frequency Conversion Main Motor (Power)	22KW	37KW	56KW
協向 (Z 輪) 电机:扭矩 Longitudinal (Z Axia) Motor: Torque	27N.m	36N.m	50N.m
横向(X、轴)电机;扭矩 Horzontel (X Axis) Motor:Torque	11N.m	27N.m	27N.m
床身导轨防护形式 Protection of Lathe Bed and Guide Rail	不锈钢的护理 Stainless Steel Protecting Cover	不锈钢防护罩 Stainless Steel Protecting Cover	不锈钢的护罩 Stainless Steel Protecting Cove
机床外形尺寸【长 × 克 × 高) Overall dimension of machine (L x W x H)	6000x2000x1400mm	6800x2000x1760mm	8600x2440x2000mm
机床重量(约) Machine weight	11500kg	15000kg	24000kg

河南百顺机械设备有限公司 A Professional Roll Processing Equipment Design and Manufacturing Enterprise Henon Boilshun Machinery Equipment Co., Ltd. 专业性的轧辊加工设备设计制造企业



Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China