



## Keyway Shaper Slotter Machine Heavy Duty B5032 Metal Slot Shaping Machine

Our Product Introduction

for more products please visit us on [lathemach.com](http://lathemach.com)

### Basic Information

- Place of Origin: China
- Brand Name: Baishun
- Certification: ISO
- Model Number: B5032
- Minimum Order Quantity: 1 Set
- Price: Negotiation
- Packaging Details: Export standard wooden case package
- Delivery Time: 20 working days
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 100Set/Sets per Month



### Product Specification

- Name: B5032 Metal Slot Shaping Machine
- Model: B5032
- Video Outgoing-inspection: Provided
- Machinery Test Report: Provided
- Function: Metal Slotting
- Controller: PLC
- Voltage: 380v/50hz Or As Customer Required
- Warranty: 1 Year
- Power (kW): 4
- Weight (KG): 3000 KG
- Highlight: Keyway Shaper Slotter, Heavy Duty Shaper Slotter



### More Images



## Product Description

### Keyway Shaper Slotting Machine Heavy Duty B5032 Metal Slot Shaping Machine

The main performance characteristics:

- 1.The working table of the machine tool is provided with three different directions of feed (longitudinal, horizontal and rotary), therefore work object go through once clamping, Several surfaces in the machine tool machining
  - 2.Hydraulic transmission mechanism with sliding pillow reciprocating motion and hydraulic feed device for working table.
  - 3.The sliding pillow has the same speed in every stroke, and the movement speed of the ram and the working table can be adjusted continuously.
  - 4.Hydraulic control table have ram commutation oil for oil reversing mechanism, In addition to hydraulic and manual feed outer,
- Even there single motor drive vertical, horizontal and rotary fast moving.
- 5.Use hydraulic feed the slotting machine, Is when the work is over turning back instantaneous feed, Therefore be better than mechanical slotting machine used drum wheel feed.

Application:

1. This machine be used for interpolation plane, forming surface and Keyway Etc. And can insert the inclination in the 10° Mold and other within the scope of etc. work matter.
2. Enterprise suitable for single or small batch production.

#### Product main technical parameters:

Specification	Unit	B5020	B5032	B5040
Max. stroke of RAM	mm	220	340	400
Ram maximum slotting length	mm	200	320	500
Ram motion frequency	times/min	32.50.80.125	20.32.50.80	20.32.50.80
Ram tilt angle	°	0-8	0-8	0-8
Ram vertical adjustment distance	mm	230	315	315
Cutter head bearing surface to the distance between the forearm bed	mm	485	600	600
Table Diameter	mm	500	630	630
The distance between the lower end of the sliding frame to work table	mm	320	490	600
Max. longitudinal moving distance of working table	mm	500	630	690
Max. transverse moving distance of working table	mm	500	560	620
Table maximum rotation angle	°	360	360	560
Vertical and horizontal table power feed range	mm	0.08-1.21	0.08-1.21	0.08-1.21
Table rotary feed range	mm	0.052-0.783	0.052-0.783	0.052-0.783
Motor power	kw	3	4	4
Motor speed	r/min	1430	960	960
Machine weight	kg	2200	3000	3700
Outline dimension	mm	1916*1305*1995	2261*1495*2245	2290*1525*2485

Machine picture:







For more detail specification please contact:



**河南百顺机械设备有限公司**  
**Henan Baishun Machinery Equipment Co., Ltd.**  
 Office Address: No. 65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China

**Ms. Elena Xie**  
 (Sales Manager)

Ph./Whatsapp: +86 17838375098

Email: elena@goodlathe.com

Tel: +86 371-55661885



**Henan Baishun Machinery Equipment Co., Ltd.**



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China