

# High Precision Spindle Vertical Type Cnc Lathe VTL Metal Cnc Turning Machine

#### **Basic Information**

• Place of Origin: Henan, China

Brand Name: BAISHUN MACHINERY


Certification: CE/ISO9001
Model Number: CK5116A
Minimum Order Quantity: 1 Set
Price: Negotiable

Packaging Details: Export standard wooden case package or

Negotiation with customers

• Delivery Time: 45 work days

Payment Terms: L/C, T/T, Western UnionSupply Ability: 20 Set/Sets per Month



#### **Product Specification**

Product Name:
 VTL Metal Cnc Turning Machine

Machine Type: CK5116AMax. Turning 1600Diameter(mm):

 Max. Height Of 1200 Workpiece(mm):

Worktable Size(mm): 1400
Max.weight Of Workpiece: 5tons
No. Of Spindles: Single
Power: 30Kw
Key Words: VTL

• Function: Heavy Duty Metal Turning

• Highlight: High Precision Spindle Cnc Lathe,

VTL Cnc Lathe, Metal Cnc Turning Machine



#### More Images





#### **Product Description**

#### High Precision Spindle Vertical Type Cnc Lathe VTL Metal Cnc Turning Machine

China Hot sale Multi-purpose CNC Vertical Turning Lathe is suitable to process ferrous metal, nonferrous metals and partial non-metallic material, and could achieve the processing of turning of the end face, inside and outside cylindrical surface, inside and outside circular conical surface and drilling, expanding, reaming of hole. Main transmission is driven by the spindle AC servo motor, hydraulic gear change and two gears step less speed regulation. Worktable is manual 4-jaw single movement chuck.

## CK5116A Heavy Duty CNC Vertical Lathe Main Features:

- 1. CNC vertical lathe, the CNC system uses Siemens 828DD system, there is a vertical tool post, the maximum machining diameter is 1600mm to 2600mm of single column vertical lathe, For CK5116 type, it is designed with the table diameter of 1400mm, and the standard maximum machining height is 1200mm.
- 2. The transmission device is a four-speed sleepless transmission, which is convenient, sensitive and reliable.
- 3. Set in the system, all gears use 40Cr grinding gears, which have the characteristics of high rotation accuracy and low noise.
- 4. The machine is suitable for high speed steel tools and carbide cutting tool processing of non-ferrous metal, black metal and nonmetal materials. On the machine can complete the following processes:Turning the inner and outer cylindrical surface of the plane; all kinds of hook face, inner and outer cone face, thread, cutting slot and cutting.

#### Machine parameter

Model	CK518	CK5112Q	CK5112A	CK5116Q	CK5120A	CK5126A
Max. turning diameter of vertical tool rest (mm)	800	1200	1200	1600	2000	2600
Working table diameter (mm)	700	1000	1000	1400	1800	2200
Max. height of work-piece (mm)	800	1000	1000	1200	1250	1400
Max. weight of work-piece (kg)	1500	1500	3200	3200	8000	8000
Range of worktable rotation speed (rpm)	30-260	20-180	6.3-200	15-160	3.2-100	2.2-70
Feeding series	Stepless	Stepless	Stepless	Stepless	Stepless	Stepless
Range of tool rest feed (mm/min)	0.25-90	0.25-90	0.8-86	0.25-90	0.8-86	0.8-86
Cross beam travel (mm)	500	1000	650	1200	890	1090
Horizontal travel of tool rest (mm)	500	700	700	900	1115	1400
Vertical travel of tool rest (mm)	450	500	650	750	800	800
Size of section of cutter bar (mm)	30*40	30*40	30*40	30*40	30*40	30*40
Main motor power (kw)	11	15	22	15	30	30

#### **Detail Machine Photo:**
























**Shipping and Delivering:** 



For more details and specifications, please contact:

Ms. Elena Xie

(Sales Manager)

Ph:/Whatsapp: +86 17838375098

Email: elena@goodlathe.com

Tel:+86 371-55661885



### Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



e lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China