

CK5123 Cnc Vertical Lathe Machine VTL Single Column Cnc Vertical Turning Turret

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- BAISHUN MACHINERY CE/ISO9001 CK5123 1 Set Negotiable Export standard wooden case package or Negotiation with customers 30-35 work days L/C, T/T, Western Union

20 Set/Sets per Month

VTL Cnc Vertical Lathe Machine

Henan, China



Product Specification

• Product Name: Cnc Vertical Turning Turret CK5123 Model: Max. Turning 2300 Diameter(mm): • Table Size(mm): 2000 • Max. Heigh Of Workpiece 1400 (mm): • No. Of Spindles: Single • Positioning Accuracy (mm): ±0.005 • Voltage: 380V • Highlight: Single Column Cnc Vertical Lathe Machine, CK5123 Cnc Vertical Lathe Machine,



More Images



CK5123 Cnc Vertical Lathe Machine VTL Single Column Cnc Vertical Turning Turret:



China Hot sale Multi-purpose CNC Vertical Turning Lathe is suitable to process ferrous metal, nonferrous metals and partial non-metallic material, and could achieve the processing of turning of the end face, inside and outside cylindrical surface, inside and outside circular conical surface and drilling, expanding, reaming of hole. Main transmission is driven by the spindle AC servo motor, hydraulic gear change and two gears step less speed regulation. Worktable is manual 4-jaw single movement chuck.

BAISHUN has strong technical force, the advanced production equipment, and the perfect administration system. Our productions have good quality, advanced technology. These single & double column lathe and NC vertical lathe have gained perfect praise by consumers since put into market.

Model	CK518	CK5112Q	CK5112A	CK5116Q	CK5120A	CK5126A
Max. turning diameter of vertical tool rest (mm)	800	1200	1200	1600	2000	2600
Working table diameter (mm)	700	1000	1000	1400	1800	2200
Max. height of work-piece (mm)	800	1000	1000	1200	1250	1400
Max. weight of work-piece (kg)	1500	1500	3200	3200	8000	8000
Range of worktable rotation speed (rpm)	30-260	20-180	6.3-200	15-160	3.2-100	2.2-70
Feeding series	Stepless	Stepless	Stepless	Stepless	Stepless	Stepless
Range of tool rest feed (mm/min)	0.25-90	0.25-90	0.8-86	0.25-90	0.8-86	0.8-86
Cross beam travel (mm)	500	1000	650	1200	890	1090
Horizontal travel of tool rest (mm)	500	700	700	900	1115	1400
Vertical travel of tool rest (mm)	450	500	650	750	800	800
Size of section of cutter bar (mm)	30*40	30*40	30*40	30*40	30*40	30*40
Main motor power (kw)	11	15	22	15	30	30

Machine parameter

Detail Machine Photo:



Shipping and Delivering:



Packing and transportation before export



We are a direct-sale lathe machine manufacturer, not a trading company, which means we can offer you the best prices.

Welcome get in touch with us:) Tel/Whatsapp:+86 18003851898 (Miss Dora)

