

# Industrial Metal Turning Vertical Type Single Column CNC Lathe Machine

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
  - Packaging Details:
  - Delivery Time:
  - Payment Terms:
  - Supply Ability:

| Henan, China   |  |
|--|--|
| BAISHUN MACHINERY  |  |
| CE/ISO9001   |  |
| CK5112   |  |
| 1 Set  |  |
| Negotiable   |  |
| Export standard wooden case package or<br>Negotiation with customers |  |
| 30-35 work days  |  |
| L/C, T/T, Western Union  |  |
| 20 Set/Sets per Month  |  |



## **Product Specification**

- Product Name:
- Machine Type:
- Max. Turning Diameter(mm):
- Max. Height Of Workpiece(mm):
- Worktable Size(mm):No. Of Spindles:
- Max.weight Of
- Workpiece(kg):
- Voltage:
- Key Words:
- Function:
- Highlight:

# CNC Lathe Machine CK5112 1200 1000

Single 1500

1000

- 380V/50Hz/3Ph
- Vertical Turning Lathe
- Metal Turning

Industrial CNC Vertical Lathe Machine, Single Column CNC Vertical Lathe Machine, Industrial Metal Turning Vertical Lathe Machine



# More Images



### **Product Description**

#### Industrial Metal Turning Vertical Type Single Column CNC Lathe Machine

China Hot sale Multi-purpose CNC Vertical Turning Lathe is suitable to process ferrous metal, nonferrous metals and partial non-metallic material, and could achieve the processing of turning of the end face, inside and outside cylindrical surface, inside and outside circular conical surface and drilling, expanding, reaming of hole. Main transmission is driven by the spindle AC servo motor, hydraulic gear change and two gears step less speed regulation. Worktable is manual 4-jaw single movement chuck.

## CK5112 CNC Vertical Lathe

#### Main Features:

1. CNC vertical lathe, the CNC system uses Siemens 828DD system, there is a vertical tool post, the maximum machining diameter can be 800mm to 2600mm of single column vertical lathe, For CK5112 type, it is designed with the table diameter of 1000mm, and the maximum machining height is 1000mm.

2. The transmission device is a four-speed sleepless transmission, which is convenient, sensitive and reliable.

3. Set in the system, all gears use 40Cr grinding gears, which have the characteristics of high rotation accuracy and low noise. 4. The machine is suitable for high speed steel tools and carbide cutting tool processing of non-ferrous metal, black metal and nonmetal materials. On the machine can complete the following processes:Turning the inner and outer cylindrical surface of the plane; all kinds of hook face, inner and outer cone face, thread, cutting slot and cutting.

#### Machine parameter

| Model  | CK518    | CK5112Q  | CK5112A  | CK5116Q  | CK5120A  | CK5126A  |
|--|----------|----------|----------|----------|----------|----------|
| Max. turning diameter of vertical tool rest (mm) | 800      | 1200     | 1200     | 1600     | 2000     | 2600     |
| Working table diameter (mm)                      | 700      | 1000     | 1000     | 1400     | 1800     | 2200     |
| Max. height of work-piece (mm)                   | 800      | 1000     | 1000     | 1200     | 1250     | 1400     |
| Max. weight of work-piece (kg)                   | 1500     | 1500     | 3200     | 3200     | 8000     | 8000     |
| Range of worktable rotation speed (rpm)          | 30-260   | 20-180   | 6.3-200  | 15-160   | 3.2-100  | 2.2-70   |
| Feeding series                                   | Stepless | Stepless | Stepless | Stepless | Stepless | Stepless |
| Range of tool rest feed (mm/min)                 | 0.25-90  | 0.25-90  | 0.8-86   | 0.25-90  | 0.8-86   | 0.8-86   |
| Cross beam travel (mm)                           | 500      | 1000     | 650      | 1200     | 890      | 1090     |
| Horizontal travel of tool rest (mm)              | 500      | 700      | 700      | 900      | 1115     | 1400     |
| Vertical travel of tool rest (mm)                | 450      | 500      | 650      | 750      | 800      | 800      |
| Size of section of cutter bar (mm)               | 30*40    | 30*40    | 30*40    | 30*40    | 30*40    | 30*40    |
| Main motor power (kw)                            | 11       | 15       | 22       | 15       | 30       | 30       |

#### **Detail Machine Photo:**











Shipping and Delivering:



Packing and transportation before export



Henan Baishun Machinery Equipment Co., Ltd. Office Address: No. 65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China

> Ms. Elena Xie (Sales Manager)

Ph:/Whatsapp: +86 17838375098

Email: elena@goodlathe.com

Tel:+86 371-55661885

•+8618939515188

HUN

Henan Baishun Machinery Equipment Co., Ltd.

sale@goodlathe.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China

lathemach.com