




High Speed Heavy Duty Dro Vertical Lathe Vertical Turning Lathe With Double Column

Our Product Introduction

for more products please visit us on lathemach.com

Basic Information

- Place of Origin: Henan, China
- Brand Name: BAISHUN MACHINERY
- Certification: CE ISO
- Model Number: CK5235
- Minimum Order Quantity: 1
- Price: \$76,000.00/sets 1-4 sets
- Packaging Details:
 1. Outside we will pack the product with plastic to prevent wet.
 2. Outside of the cnc vertical lathe machine will be packed by strong wooden pallet.
- Delivery Time: 45 Working days
- Supply Ability: 20 Set/Sets per Month



Product Specification

- Max. Length Of Workpiece (mm): 2500
- Max. Spindle Speed (r.p.m): 90 R.p.m
- Machining Capacity: Medium Duty
- Spindle Bore(mm): 105
- Width Of Bed (mm): 250 Mm
- Spindle Motor Power(kW): 55
- No. Of Spindles: Twin
- Number Of Axes: 2
- Travel (X Axis)(mm): 1900 Mm
- Travel (Z Axis)(mm): 1250 Mm
- Positioning Accuracy (mm): ± 0.005
- Repeatability (X/Y/Z) (mm): ± 0.003
- Dimension(L*W*H): 6150*4400*5330mm
- Voltage: 380V



More Images



Product Description

High Speed Heavy Duty Dro Vertical Lathe Vertical Turning Lathe With Double Column

The double column vertical lathe is a cutting-edge piece of equipment that combines mechanical, electrical, and hydraulic components. It incorporates modern design principles and manufacturing techniques, leveraging CAD optimization and state-of-the-art components from both domestic and international sources. The machine boasts a robust structure, offering exceptional strength, high static and dynamic stiffness, precise machining capabilities, heavy load capacity, efficiency, durability, and reliable operation. All major technical specifications of the machine parts comply with national standards.

1. It is mostly used to process middle-diameter tire mould and flanges, various valves and pipelines, pressure vessels, screw propeller, steamer machine accessories, plastic mould, shafts and other work-piece.
2. It is suitable for processing the internal/external cylindrical surface, conical surface, end face etc
3. Spindle bearings use domestic famous-brand company products.
4. Head stock takes symmetrical structure to make thermal deformation be even, avoiding the spindle center generates offsets.
5. Gears in head stock and guide way are processed by quenching to ensure accurate transmission and high rigidity.
6. Vertical lathe table inlaid with zinc alloy wear-resistant guide guard and can access pressure oil (0.2-0.4MPa) between the rails for improving load-carrying ability of workbench.
7. Vertical lathe casting has passed through strict artificially aged and vibration aging in order to make sure the rigidity and stability of lathe.

Based on excellent processing equipment, strong technical force, perfect inspection way, and inpectable management system. BAISHUN Machine has passed National ISO9001:2008 Quality Management System Certification.

Machine parameter


Specifications	Unit	CK5225	CK5231	CK5240Q	CK5240
Max.turning diameter	mm	2500	3150	4000	4000
Max. height of work piece	mm	1600/2000/2500	1600/2000/2500	1600/2000/2500	1600/2000/2500
Max. weight of work piece	T	10/20	10/20	10/20	32
Worktable diameter	mm	2250	2830	2830/3150	3200/3600
Range of table speeds	r/min	2-63	2-63	2-63	2-63
Steps		16	16	16	16
Max torque of work table	KN.m	63	63	63	100
Rapid traverse of rail head	mm/min	4000	4000	4000	4000
Ram vertical travel of right railhead	Kn	35	35	35	40
Ram vertical travel of left railhead	kn	30	30	30	30
Range cutting force of right railhead	mm/min	1-50	1-50	1-50	1-50
Range cutting force of right railhead	mm/min	0.1-1000	0.1-1000	0.1-1000	0.1-1000
Travel of arm	mm	1000	1000	1000	1250
Section of arm	mm	255×200	255×200	255×200	240×240
Swivel of left and right railhead	°	±30°	±30°	±30°	±30°
Section of tool	mm	40×50	40×50	40×50	50×50
Power of main motor	Kw	55	55	55	75
Overall dimensions	cm	569×470×480/520	605×440×493/533	690×510×480/520	690×510×480/520

Product photos

BAISHUN

VERTICAL LATHE CK5235

High efficiency | Automatic | Reliable | High precision



High Quality /PRODUCT

Factory Diresct /SELLING

Whatsapp: +86 18003851898

Email: dora@bsmachinery.com



Product Details Display

01



COMFORT
VENTILATION

WORKTABLE

Worktable has high rotation precision and large load capacity.

ALL RIGHTS RESERVED BY COMFORT VENTILATION
PROPERTY OF COMFORT VENTILATION
WWW.COMFORTVENTILATION.COM



02

COMFORT
VENTILATION

ELECTRIC TOOL POST

Clients can choose
4,5,6 station
electric tool post.

ALL RIGHTS RESERVED BY COMFORT VENTILATION
PROPERTY OF COMFORT VENTILATION
WWW.COMFORTVENTILATION.COM



03

COMFORT
VENTILATION

COLUMN/ CROSS BEAM

High frequency column
and beamguide,
hardness HRC-55
degree.





04
COMFORT
VENTILATION

CONTROL SYSTEM

Standard with
GSK980TDi control
Optional: Siemens,
Fanuc, Syntec ect.



Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China