

Henan, China

CE/ISO9001

CK5112 1 Set

Negotiable

30-35 work days

BAISHUN MACHINERY

Negotiation with customers

L/C, T/T, Western Union

20 Set/Sets per Month

Export standard wooden case package or

CNC Carousel Vertical Lathe Torno Metal Processing Heavy Duty Lathe Machine

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Product Name:	CNC Carousel Vertical Lathe Torno
Machine Type:	CK5112
 Max. Turning Diameter(mm): 	1200
 Max. Height Of Workpiece(mm): 	1000
• Worktable Size(mm):	1000
 No. Of Spindles: 	Single
 Positioning Accuracy (mm): 	±0.005
• Voltage:	380V
 Key Words: 	Lathe Torno
• Function:	Metal Turning
• Highlight:	Metal Processing Vertical Lathe Machine, Heavy Duty Vertical Lathe Machine, CNC Carousel Vertical Lathe Machine



More Images







Product Description

CNC Carousel Vertical Lathe Torno Metal Processing Heavy Duty Lathe Machine:

China Hot sale Multi-purpose CNC Vertical Turning Lathe is suitable to process ferrous metal, nonferrous metals and partial non-metallic material, and could achieve the processing of turning of the end face, inside and outside cylindrical surface, inside and outside circular conical surface and drilling, expanding, reaming of hole. Main transmission is driven by the spindle AC servo motor, hydraulic gear change and two gears step less speed regulation. Worktable is manual 4-jaw single movement chuck.

CK5112 CNC Vertical Lathe

Main Features:

1. CNC vertical lathe, the CNC system uses Siemens 828DD system, there is a vertical tool post, the maximum machining diameter can be 800mm to 2600mm of single column vertical lathe, For CK5112 type, it is designed with the table diameter of 1000mm, and the maximum machining height is 1000mm.

2. The transmission device is a four-speed sleepless transmission, which is convenient, sensitive and reliable.

3. Set in the system, all gears use 40Cr grinding gears, which have the characteristics of high rotation accuracy and low noise. 4. The machine is suitable for high speed steel tools and carbide cutting tool processing of non-ferrous metal, black metal and nonmetal materials. On the machine can complete the following processes:Turning the inner and outer cylindrical surface of the plane; all kinds of hook face, inner and outer cone face, thread, cutting slot and cutting.

Machine parameter

Model	CK518	CK5112Q	CK5112A	CK5116Q	CK5120A	CK5126A
Max. turning diameter of vertical tool rest (mm)	800	1200	1200	1600	2000	2600
Working table diameter (mm)	700	1000	1000	1400	1800	2200
Max. height of work-piece (mm)	800	1000	1000	1200	1250	1400
Max. weight of work-piece (kg)	1500	1500	3200	3200	8000	8000
Range of worktable rotation speed (rpm)	30-260	20-180	6.3-200	15-160	3.2-100	2.2-70
Feeding series	Stepless	Stepless	Stepless	Stepless	Stepless	Stepless
Range of tool rest feed (mm/min)	0.25-90	0.25-90	0.8-86	0.25-90	0.8-86	0.8-86
Cross beam travel (mm)	500	1000	650	1200	890	1090
Horizontal travel of tool rest (mm)	500	700	700	900	1115	1400
Vertical travel of tool rest (mm)	450	500	650	750	800	800
Size of section of cutter bar (mm)	30*40	30*40	30*40	30*40	30*40	30*40
Main motor power (kw)	11	15	22	15	30	30

Detail Machine Photo:















Shipping and Delivering:



Packing and transportation before export



Henan Baishun Machinery Equipment Co., Ltd. Office Address: No. 65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China

> Ms. Elena Xie (Sales Manager)

Ph:/Whatsapp: +86 17838375098

Email: elena@goodlathe.com

Tel:+86 371-55661885

•+8618939515188

HUN

Henan Baishun Machinery Equipment Co., Ltd.

sale@goodlathe.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China

lathemach.com