

Vertical Machining Center 3axis Taiwan Linear Guideway Vertical Lathe Machinery VMC850

Basic Information

Place of Origin: Henan, China
Brand Name: BAISHUN
Certification: ISO
Model Number: VMC850
Minimum Order Quantity: 1 set
Price: Negotiation

Packaging Details: Export standard wooden case or as

customers' requirement

• Delivery Time: 45 work days

Payment Terms: T/T, L/C, Western Union
 Supply Ability: 50 Set/Sets per Month



Product Specification

Product Name: Vertical Lathe Machinery VMC850

X/Y/Z Travel (X) (mm): 800/500/600
 Table Size (mm): 1050*500
 Max. Table Load(kg): 300 Kg
 Spindle Taper: BT40

Keywords: Vertical Lathe

Usage: Metal Turning And Milling

Machine Weight (T): 3 T

• Max.speed Of Spindle: 8000r/min

• Dimension(L*W*H): 2100*1950*2200mm

Highlight: VMC850 Vertical Machining Center,
 Taiwan Linear Guideway Vertical Machining

Center

, 3 Axis Vertical Machining Center



More Images







Product Description

Vertical Machining Center 3axis Taiwan Linear Guideway Vertical Lathe Machinery VMC850

Product Description

Vertical Milling Centers (VMC) are widely utilized in manufacturing sectors such as automotive, aerospace, and electronics, serving as crucial equipment for producing intricate precision parts. Their primary components, including the base, saddles, worktables, columns, and spindle housings, are all constructed from HT300 cast iron. The base features a box-type structure, complemented by a compact and rationally designed symmetrical rib structure, ensuring the high rigidity and bending resistance of the foundational elements. A-type bridge struts and internal grid-like ribs robustly guarantee the stiffness and precision of the Z-axis during heavy cutting. Furthermore, these fundamental parts are manufactured using resin sand casting and undergo aging treatment to assure the long-term stability of the machine tool's performance.









Machine Parameter

Table(mm)	Model	VMC550	VMC650	VMC850	VMC1050		
Max.table load(kg) 300 450 600 600 X/Y/Z axis travel(mm) 550"350"500 650"400"500 800"500"600 1000"500"600 Diatance between spindle center and column guide surface(mm) 419 476 560 560 Diatance between spindle face and worktable face(mm) 100-600 100-600 140-740 140-740 X/Y/Z Max.feed speed(mm/min) 20/20/15 24/24/20 20/20/15 20/20/15 X/Y/Z Max.rapid traverse 8000 8000 8000 8000 Max.speed of spindle(r/min) BT40 BT40 BT40 BT40 The spindle taper hole(type) BT40 BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection 5.18*125 5-18*90 5-18*90 5-18*90 Slot(mm) Repeat ±0.004 ±0.004 ±0.004 ±0.004 ±0.004 Aax.tool lengthr(mm) 250/300							
X/Y/Z axis travel(mm)							
Travel(mm)							
Diatance between spindle center and column guide surface(mm)	travel(mm)						
Spindle center and column guide surface(mm)		419	476	560	560		
column guide surface(mm) 100-600 100-600 140-740 140-740 Diatance between spindle face and worktable face(mm) 10000 10000 10000 10000 X/Y/Z Max.feed speed(mm/min) 20/20/15 24/24/20 20/20/15 20/20/15 X/Y/Z Max.rapid traverse 8000 8000 8000 8000 Max.speed of spindle (r/min) BT40 BT40 BT40 The spindle taper hole(type) BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) Direct connection 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Two linear one hard guide Linear guide hard guide Linear guide hard guide Linear guide hard guide Linear guide hard guide 25.18*90 5-18*90 Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool length(mm) 250/300 250/300 250/300							
Surface(mm)							
spindle face and worktable face(mm) 10000							
worktable face(mm) 10000 10000 10000 X/Y/Z Max.feed speed(mm/min) 20/20/15 24/24/20 20/20/15 20/20/15 X/Y/Z Max.rapid traverse 8000 8000 8000 8000 8000 Max.speed of spindle (r/min) 8000 8000 8000 8000 8000 The spindle taper hole(type) BT40 BT40 BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Einear guide Linear guide Linear guide X/Y/Z Guide way type Linear guide Two linear one hard guide Linear guide 5-18*90 Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10	Diatance between	100-600	100-600	140-740	140-740		
face(mm) X/Y/Z Max.feed speed(mm/min) 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 10000 20/20/15 <	spindle face and						
X/Y/Z Max.feed speed(mm/min) 10000 <td< td=""><td>worktable</td><td></td><td></td><td></td><td></td></td<>	worktable						
speed(mm/min) 20/20/15 24/24/20 20/20/15 20/20/15 Max.speed of spindle(r/min) 8000 8000 8000 8000 The spindle taper hole(type) BT40 BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection XY/Z Guide way type Linear guide Two linear one hard guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11 11	face(mm)						
X/Y/Z Max.rapid traverse 20/20/15 24/24/20 20/20/15 20/20/15 Max.speed of spindle(r/min) 8000 8000 8000 8000 The spindle taper hole(type) BT40 BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Direct quide Linear guide Linear guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11	X/Y/Z Max.feed	10000	10000	10000	10000		
traverse Max.speed of spindle(r/min) 8000 8000 8000 8000 8000 The spindle taper hole(type) BT40 BT40 BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Direct connection X/Y/Z Guide way type Linear guide Two linear one hard guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 Electric 10 10 11 11							
Max.speed of spindle(r/min) 8000 8000 8000 8000 The spindle taper hole(type) BT40 BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Two linear one hard guide Linear guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11 11	X/Y/Z Max.rapid	20/20/15	24/24/20	20/20/15	20/20/15		
spindle (r/min) BT40 BT401.0/1.0/2.0 BT401.0/1.0/2.0 BT401.0/1.0/2.0 <th< td=""><td></td><td></td><td></td><td></td><td></td></th<>							
The spindle taper hole(type) BT40 BT40 BT40 BT40 Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Linear guide Linear guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11 11		8000	8000	8000	8000		
Nole(type) Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection							
Spindle motor(kw) 3.7/5.5 5.5/7.5 7.5/11 7.5/11 X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Linear guide Linear guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11		BT40	BT40	BT40	BT40		
X/Y/Z axis servo motor(kw) 1.0/1.0/1.5 1.0/1.0/1.5 1.0/1.0/2.0 1.0/1.0/2.0 X/Y/Z motor connection Direct connection Linear guide Linear guide <td< td=""><td></td><td></td><td></td><td></td><td></td></td<>							
motor(kw) Direct connection X/Y/Z motor connection Direct connection X/Y/Z Guide way type Linear guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11							
X/Y/Z motor connection Direct connection X/Y/Z Guide way type Linear guide Two linear one hard guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11		1.0/1.0/1.5	1.0/1.0/1.5	1.0/1.0/2.0	1.0/1.0/2.0		
connection X/Y/Z Guide way type Linear guide Two linear one hard guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11							
X/Y/Z Guide way type Linear guide hard guide Linear guide hard guide Linear guide hard guide Linear guide Linear guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11		Direct connection					
type hard guide Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11				1			
Worbench T slot(mm) 3-18*105 3-18*125 5-18*90 5-18*90 Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11	,	Linear guide		Linear guide	Linear guide		
slot(mm) L ±0.004 <td>type</td> <td></td> <td>hard guide</td> <td></td> <td></td>	type		hard guide				
slot(mm) L ±0.004 <td>Worbench T</td> <td>3-18*105</td> <td>3-18*125</td> <td>5-18*90</td> <td>5-18*90</td>	Worbench T	3-18*105	3-18*125	5-18*90	5-18*90		
Repeat accuracy(mm) ±0.004 ±0.004 ±0.004 ±0.004 Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11		0 .0 .00	0 .0 .20		0.000		
accuracy(mm) 8 Max.tool wight(kg) 7 Max.tool length(mm) 250/300 Electric 10 10 11 11		±0.004	±0.004	±0.004	±0.004		
Max.tool wight(kg) 7 7 8 8 Max.tool length(mm) 250/300 250/300 250/300 Electric 10 10 11 11							
Max.tool length(mm) 250/300 250/300 250/300 250/300 Electric 10 10 11 11		7	7	8	8		
length(mm) 10 11 11		250/300	250/300	250/300	250/300		
Electric 10 10 11 11	length(mm)						
capacity(kVA)		10	10	11	11		
	capacity(kVA)						

Weight (kg)	3000	4500	5700	6000
Dimension(L*W*H	2100*1950*22	2300*2200*24	2700*2400*27	2920*2400*27
mm)	00	00	00	00

Company Introduction

Henan Baishun Machinery Equipment Co., Ltd is a professional manufacturer, which especially work for Slotting machine, Vertical lathe machine, CNC Vertical lathe machine, CNC Horizontal lathe machine, Roll lathe machine, Gear hobbing machine, Pole erection machine, Shredder machine, etc. With 14 years experience for lathe machines, we have export our products to Peru, Brazil, Chile, Mexico, Italy, Indonesia, Sri Lanka, Russia, and Uzbekistan.ect.

Our company attaches great importance to international technical exchanges and cooperation, has introduced advanced technology and craft from United States, Germany, Australia and other countries, establishes the international advanced production lines and first-class modern testing base. Welcome all friends visiting and communicating and cooperating.

Related Products

Our Services

Our Services

We can provides 7x24-hour online pre-sale service, engineer follow-up order service, and logistics delivery operation service. And also we can provide installation services. In addition, with more than 10 years experience of various markets, we can help customers successfully complete a series of services from purchasing to goods Customs clearance, thereby saving times and also reducing customers' costs in all aspects.

Our advantage:

- 1: With CE, ISO certification.
- 2: Full production tracking.
- 3: Professional engineers can guarantee the highest quality.
- 4: More suppliers as alternatives, guarantee your lowest and competitive price.
- 5; Sales fstaff with more than 10 years experience, will answer your pre-sales and after-sales questions.
- 6: OEM production is available, to meet customer needs
- 7. Low MOQ (1 unit) is available.
- 8. 24 hours technical support.

Warranty period:

During warranty period (one year), if you have any parts broken because of qulity problem,we will supply to you free of charge by express.

Out of warranty period, if you have any question, you can contact us, we will supply our best service to you as usual.

- 1. Technical support online service provided.
- 2. Technical files service provided.
- 3. Machine operation video provided
- 4. On-site training service provided.
- 5. Spare parts replacement and repair service provided.
- 6. All of the questions will be replied within 24 hours

Contact

Welcome to contact!!



Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



(athemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China