



Full Enclosure BK7032 CNC Slotting Machine Adjustable Ram Speed CNC X Y Axis Table Feeding Slotter

Our Product Introduction

for more products please visit us on lathemach.com

Basic Information

- Place of Origin: China
- Brand Name: Baishun
- Certification: ISO
- Model Number: BK7032
- Minimum Order Quantity: 1 Set
- Price: Negotiation
- Packaging Details: Export standard wooden case package
- Delivery Time: 20 working days
- Payment Terms: T/T,L/C,Western Union
- Supply Ability: 100Set/Sets per Month



Product Specification

- Name: BK7032 CNC Slotting Machine
- Model: BK7032
- Max Ram Length: 320mm
- Ram Adjustment Stroke: 220mm
- Ram Movements: 10~200times/min
- Working Desk Size: 400mm
- Main Motor Power: 11kW
- Max.load Capacity: 350kg
- Key Words: CNC Slotting Machine
- Highlight: CNC slotting machine full enclosure, BK7032 slotter adjustable ram speed, CNC X Y axis table feeding slotter



More Images



Product Description

Full Enclosure BK7032 CNC Slotting Machine Adjustable Ram Speed CNC X Y Axis Table Feeding Slotter:

This CNC Slot machines are used for interpolation plane, forming surface and Keyway Etc. And can insert the inclination in the 10° Mold and other within the scope of etc. work matter, Enterprise suitable for single or small batch production.

The main performance characteristics:

- 1.The working table of the machine tool is provided with three different directions of feed (longitudinal, horizontal and rotary), therefore work object go through once clamping, Several surfaces in the machine tool machining
- 2.Hydraulic transmission mechanism with sliding pillow reciprocating motion and hydraulic feed device for working table.
- 3.The sliding pillow has the same speed in every stroke, and the movement speed of the ram and the working table can be adjusted continuously.
- 4.Hydraulic control table have ram commutation oil for oil reversing mechanism, In addition to hydraulic and manual feed outer, Even there single motor drive vertical, horizontal and rotary fast moving.
- 5.Use hydraulic feed the slotting machine, Is when the work is over turning back instantaneous feed, Therefore be better than mechanical slotting machine used drum wheel feed.

Application:

1. This machine be used for interpolation plane, forming surface and Keyway Etc. And can insert the inclination in the 10° Mold and other within the scope of etc. work matter.
2. Enterprise suitable for single or small batch production.

Product main technical parameters:

BK7032	Specification	Movement	positioning accuracy	Load accuracy
Max.slotting length	320mm			
Max.installation size of workpiece	300mm			
Max.load capacity	350kg			
Max.cutting width	0.5-20mm			
Ram reciprocating speed per minute	10—200			
Ram vertical adjustment range	220mm			
Max. tool holder size	Φ40			
Diameter of rotary table	400mm	C axis		
Longitudinal travel distance of table	600mm	Y axis	0.0015mm	0.01mm
Lateral travel distance of table	100mm	X axis	0.003mm	0.01mm
Longitudinal and lateral feed range of table	0.01-1mm Step less	XC axis	/	/
Height from plug to work surface	450mm	Z		
Permanent magnet servo brake motor	11kw step less	Z axis	0.1mm	0.3mm
CNC SYSTEM	GSK980MDi			
Rail refueling pump	Automatic refueling pump			
Casting material	HT250			
Dimension	2500*2100*2870mm			
Gross Weight	5000KG			

Machine picture:





For more detail specification please contact:



河南百顺机械设备有限公司
Henan Baishun Machinery Equipment Co., Ltd.
Office Address: No. 65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China

Ms. Elena Xie
(Sales Manager)

Ph:/Whatsapp: +86 17838375098

Email: elena@goodlathe.com

Tel:+86 371-55661885



Henan Baishun Machinery Equipment Co., Ltd.



+8618939515188



sale@goodlathe.com



lathemach.com

No.65, Tianming Road, Jinshui District, Zhengzhou City, Henan Province, China